

DATA SHEET

TABLETOP MACHINE MAX 36



TECHNICAL DATA

Inner chamber dimensions	815 x 390 x 105 mm*
External dimensions	910 x 580 x 410 mm*
Seal length	360 mm 720 mm 790 mm
Vacuum pump	21 m ³ /h 40 m ³ /h**
Control system	Z 2001 SENSOR
Weight	95 kg 102 kg**
Power supply	1 phase, 230 V, 50 Hz***



* width x depth x height
 ** equipped with a Becker pump
 *** special voltages on request

All dimensions are approximate.
 We reserve the right to make technical changes
 and improvements without notice.

INSPIRING VACUUM TECHNOLOGY

- Perfect finish
- Easy handling
- Precise control system
- Maximum durability
- Wide range of applications
- 99% vacuum
- Proof and reliable sealing
- Simple cleaning
- Service-friendly

MACHINE STRUCTURE



Cover closing mechanism



Insertion plates for volume reduction and height regulation



Cable-free sealing system



High-quality, stable acrylic lid

Protected suction unit

Stainless steel design

User-friendly digital control Z 2001 SENSOR

Non-slip rubber feet


Plug-and-play unit with integrated vacuum pump

CONTROL SYSTEM


Our Z 2001 SENSOR control system is equipped with a precision sensor and allows precise adjustment of important operation parameters: vacuum, gas and sealing.

Benefits:


- 5 shortcut buttons
- H₂O program for automatic packaging of liquid products
- Maximum vacuum to minimize germ growth
- Service program for the longevity of the machine
- Marinade program for HORECA-use (Hotel, Restaurant, Catering)
- 99-program memory




Ultimate pressure controlled evacuation with auto-stop function



Service program



Marinade program, outgassing program



VACUUM PUMP

Our Boss vacuum packaging machines are equipped with powerful oil-lubricated rotary vane vacuum pumps made by companies Busch or Becker.


Technical data	Busch	Becker
Nominal pumping speed	21 m ³ /h	40 m ³ /h
Ultimate pressure (mBar)	2	1
Nominal motor rating (kW)*	~ 0,75	~ 1,1
Nominal motor speed (U/min)	3000	2800
Noise level (ISO 2151) (dB)	62	64
Oil capacity (liter)	0,5	0,5

* depends on the voltage supply



SEALING SYSTEMS


Double sealing




Simple cut-off sealing



Double flat wire:
6 x 0,3 mm



Round wire: 1,0 mm Ø
Flat wire: 3 x 0,2 mm



ACCESSORIES

1. Gas flush device (short bar: 2 nozzles / long bar: 4 nozzles)
2. Mobile machine support with storage space (stainless steel)
3. Slanted bag holder for packaging of liquids (stainless steel)
4. Sucking device for standardized catering boxes
5. Programmable sensor control system Z 3000 incl. high pressure seal
6. Set of wearing parts (teflon, wire, lid gasket, silicone for pressure bar)
7. Packaging (stable cardboard box on wooden pallet)

