

DATA SHEET

FLOOR-STANDING MACHINE MAX-F 50



TECHNICAL DATA



Inner chamber dimensions	530 x 545 x 180 mm*
External dimensions	650 x 700 x 1000 mm*
Seal length	500 mm
Vacuum pump	25 m ³ /h 40 m ³ /h XL** 63 m ³ /h
Control system	Z 2001 SENSOR
Weight	112** kg 125 kg 145 kg
Power supply	3 phases, 230 / 400 V, 50 Hz***




* width x depth x height
 ** equipped with a Becker pump
 *** special voltages on request

All dimensions are approximate.
 We reserve the right to make technical changes
 and improvements without notice.

INSPIRING VACUUM TECHNOLOGY

- Perfect finish
- Easy handling
- Precise control system
- Maximum durability
- Wide range of applications
- 99% vacuum
- Proof and reliable sealing
- Simple cleaning
- Service-friendly

MACHINE STRUCTURE



Cover closing mechanism



Insertion plates for volume reduction and height regulation



Cable-free sealing system



High-quality, stable acrylic lid

Protected suction unit

Stainless steel design

User-friendly digital control Z 2001 SENSOR

Mobile, plug-and-play unit with integrated vacuum pump


Four robust stainless steel rollers of which two are lockable

CONTROL SYSTEM


Our Z 2001 SENSOR control system is equipped with a precision sensor and allows precise adjustment of important operation parameters: vacuum, gas and sealing.

Benefits:


- 5 shortcut buttons
- H₂O program for automatic packaging of liquid products
- Maximum vacuum to minimize germ growth
- Service program for the longevity of the machine
- Marinade program for HORECA-use (Hotel, Restaurant, Catering)
- 99-program memory




Ultimate pressure controlled evacuation with auto-stop function



Service program



Marinade program, outgassing program



VACUUM PUMP

Our Boss vacuum packaging machines are equipped with powerful oil-lubricated rotary vane vacuum pumps made by companies Busch or Becker.

Technical data	Busch		Becker
Nominal pumping speed	25 m ³ /h	63 m ³ /h	40 m ³ /h XL
Ultimate pressure (mBar)	0,1	0,1	1
Nominal motor rating (kW)*	~ 0,75	~ 1,5	~1,1
Nominal motor speed (U/min)	1500	1500	2800
Noise level (ISO 2151) (dB)	62	65	67
Oil capacity (liter)	1	1	1

* depends on the voltage supply




German made





SEALING SYSTEMS


Double sealing




Simple cut-off sealing



Double flat wire:
6 x 0,3 mm



Round wire: 1,2 mm Ø
Flat wire: 4 x 0,2 mm



ACCESSORIES

1. Gas flush device with 3 nozzles
2. Slanted bag holder for packaging of liquids (stainless steel)
3. Sucking device for standardized catering boxes
4. Programmable sensor control system Z 3000 incl. high pressure seal weld
5. Slow air release (only available in combination with sensor control system Z 3000)
6. Stainless steel lid (usable height 185 mm)
7. Top/bottom welding (only available in combination with stainless steel lid)
8. Inspection glass in the lid (only available in combination with stainless steel lid)
9. Set of wearing parts (teflon, wire, lid gasket, silicone for pressure bar)
10. Packaging (stable cardboard box on wooden pallet)

